

Cavity Directional Couplers

- Frequency Range 0.35 to 3.5GHz.
- Military, Space and Commercial Applications, Meet RoHS Standard.
- Good temperature behavior ,High aseismatic capability.
- Custom Design Available Upon Request.



Part Number	Freq.Range (MHz)	Coupling/Norminal Input↔P2(dB)	Inband Ripple (dB)	Insertion Loss Max.(dB)	VSWR Max.	Directivity Min.(dB)	Power (W)	Size LxWxH (mm)	Connector Type	Temp. Range (°C)
DPVCP03527A5	350-2700	-5	±0.8	2.1	1.25	20	200	230x43x18	N	-25~+75
DPVCP03527A6		-6	±0.8	1.6	1.25					
DPVCP03527A7		-7	±0.8	1.5	1.25					
DPVCP03527A8		-8	±0.8	1.2	1.25					
DPVCP03527A10		-10	±1.0	0.8	1.25					
DPVCP03527A15		-15	±1.0	0.4	1.25					
DPVCP03527A20		-20	±1.0	0.22	1.25					
DPVCP04786A5	470-860	-5	±0.5	2.0	1.2	20	200	144x43x18	N	-25~+75
DPVCP04786A7		-7	±0.6	1.3	1.2					
DPVCP04786A10		-10	±0.8	0.8	1.2					
DPVCP0727A5	700-2700	-5	±0.8	2.1	1.25	20	200	119x42x18	N	-25~+75
DPVCP0727A6		-6	±0.8	1.6	1.25					
DPVCP0727A7		-7	±0.8	1.5	1.25					
DPVCP0727A8		-8	±0.8	1.2	1.25					
DPVCP0727A10		-10	±1.0	0.8	1.25					
DPVCP0727A15		-15	±1.0	0.4	1.25					
DPVCP0727A20		-20	±1.0	0.22	1.25					

Cavity Directional Couplers

Part Number	Freq.Range (MHz)	Coupling/Norminal Input↔P2(dB)	Inband Ripple (dB)	Insertion Loss Max.(dB)	VSWR Max.	Directivity Min.(dB)	Power (W)	Size LxWxH (mm)	Connector Type	Temp. Range (°C)
DPVCP0735A5	700-3500	-5	±0.8	2.1	1.25	20	200	134x42x18	N	-25~+75
DPVCP0735A6		-6	±0.8	1.6	1.25					
DPVCP0735A7		-7	±0.8	1.5	1.25					
DPVCP0735A8		-8	±0.8	1.2	1.25					
DPVCP0735A10		-10	±1.0	0.8	1.25					
DPVCP0735A15		-15	±1.0	0.4	1.25					
DPVCP0735A20		-20	±1.0	0.22	1.25					
DPVCP0825A5	800-2500	-5	±0.6	2.0	1.2	20	200	119x42x18	N	-25~+75
DPVCP0825A6		-6	±0.6	1.6	1.2					
DPVCP0825A7		-7	±0.6	1.5	1.2					
DPVCP0825A8		-8	±0.6	1.2	1.2					
DPVCP0825A10		-10	±0.8	0.8	1.2					
DPVCP0825A15		-15	±0.8	0.4	1.2					
DPVCP0825A20		-20	±0.8	0.22	1.2					
DPVCP0825A30		-30	±1.5	0.2	1.2					
DPVCP0825A40		-40	±2.0	0.2	1.2					
DPVCP0827A5	800-2700	-5	±0.8	2.1	1.2	20	200	134x42x18	N	-25~+75
DPVCP0827A6		-6	±0.8	1.6	1.2					
DPVCP0827A7		-7	±0.8	1.5	1.2					
DPVCP0827A8		-8	±0.8	1.2	1.2					
DPVCP0827A10		-10	±1.0	0.8	1.2					
DPVCP0827A15		-15	±1.0	0.4	1.2					
DPVCP0827A20		-20	±1.0	0.22	1.2					



DPV CO

17A16, Jueshi Building, Jiabin Road, Luohu District, Shenzhen 518001, China.

Tel : +86-755-88877009 Fax : +86-755-88877006

E-mail: sales@dpv.co Website: www.dpv.co www.dpvr.com

REV.B