

Dual Junction Coaxial Isolators

- Frequency Range 60MHz – 2.5GHz, Up to 80dB Isolation.
- Military, Space and Commercial Applications, Meet RoHS Standard.
- Good temperature behavior, High aseismatic capability.
- Custom Design Available Upon Request.



Part Number	Freq.Range	Band Width (MHz)	Insertion Loss Max.(dB)	Isolation Min.(dB)	VSWR Max.	FWD/REV Powe (W)	Size L×W×H (mm)	Connector Type	Temp.Range (°C)
DPVCDI120A	70-120MHz	10	1.2	40	1.25	100/30	120×60×27.5	N/SMA	-20~+65
	120-220MHz	30	1.2	40	1.25				
	87-108MHz	Full	1.2	40	1.25				
	85-135MHz	Full	2.4	36	1.3				
	130-180MHz	Full	1.6	36	1.3				
DPVCDI120B	70-120MHz	10	1.2	40	1.25	100/100	120×75×27.5	N/SMA	-20~+65
	120-220MHz	30	1.2	40	1.25				
	87-108MHz	Full	1.2	40	1.25				
	85-135MHz	Full	2.4	36	1.3				
	130-180MHz	Full	1.6	36	1.3				
DPVCDI104A	170-220MHz	10	1.0	40	1.2	300/30	104×57.5×22	N/SMA	-30~+70
	220-300MHz	30	1.0	40	1.2				
DPVCDI104B	170-220MHz	10	1.0	40	1.2	300/150	104×77.5×22	N/SMA	-30~+70
	220-300MHz	30	1.0	40	1.2				
DPVCDI96A	280-450MHz	30	0.6	45	1.2	300/30	96×50×26.5	N/SMA	-30~+70
	450-1300MHz	100	0.8	40	1.2				
DPVCDI96B	280-450MHz	30	0.6	45	1.2	400/250	96×78×26	N/SMA	-30~+70
	450-1300MHz	100	0.8	40	1.2				
DPVCDI56A	0.7-1.0GHz	30	0.6	45	1.2	200/30	56×28.5×15	N/SMA	-30~+70
	1.0-3.1GHz	100	0.6	45	1.2				
	1.3-3.1GHz	200	0.8	40	1.2				
DPVCDI42A	3.0-4.0GHz	200	0.6	45	1.2	100/20	42×24.5×15	N/SMA	-30~+70
		300	0.7	40	1.25				
DPVCDI39A	3.5-7.0GHz	300	0.6	45	1.2	60/20	39×28×15	N/SMA	-30~+70
		600	0.8	40	1.25				
DPVCDI24A	7.0-20.0GHz	500	0.6	45	1.2	60/5	24×20×13	SMA	-30~+70
		2000	0.8	40	1.25				