

Surface Mount Isolators

- ✦ Frequency Range 600MHz - 3.8GHz,from 5% to Full Bandwidth.
- ✦ Military, Space and Commercial Applications, Reflowable.
- ✦ Low insertion Loss,High Isolation,High power handling.
- ✦ Custom Design Available Upon Request.



Part Number	Frequency Range (GHz)	Bandwidth Max.	Insertion Loss Max.(dB)	Isolation Min. (dB)	VSWR Max.	FWD/REV Power (W)	Size D×H (mm)	Temp. Range (°C)
DPVSI24A	600-1300	5%	0.35	23	1.2	100/5	Φ24.2×6.5	-30~+70
		10%	0.4	20	1.25			
DPVSI18A	1300-3800	5%	0.35	23	1.2	100/5	Φ18.2×6.5	-30~+70
		10%	0.4	20	1.25			
DPVSI27A	925-960	Full	0.3	23	1.2	100/5	Φ27×10	-30~+85
DPVSI22A	2110-2170	Full	0.3	23	1.2	100/5	Φ22.9×8.9	-30~+85



DPV CO

17A16,Jueshi Building, Jiabin Road, Luohu District, Shenzhen 518001, China.

Tel : +86-755-88877009 Fax : +86-755-88877006

E-mail: sales@dpv.co Website: www.dpv.co www.dpvr.com

REV.B