

Cavity Power Splitters

- Frequency Range 0.3 to 3.5GHz.
- Military, Space and Commercial Applications, Meet RoHS Standard.
- Good temperature behavior ,High aseismatic capability.
- Custom Design Available Upon Request.



Part Number	Freq.Range (MHz)	Description	Insertion Loss Max.(dB)	VSWR Max.	Input Power (W)	Impedance (Ω)	Size LxWxH (mm)	Connector Type	Temp.Range ($^{\circ}$ C)
DPVSP0310A2	300-1000	2	3.1	1.2	500	50	368.3x25x25	N	-40~+80
DPVSP0310A3		3	5.1	1.2			480.9x25x25		
DPVSP0310A4		4	6.3	1.25			480.9x25x25		
DPVSP03527A2	350-2700	2	3.1	1.25	500	50	460.5x25x25	N	-40~+80
DPVSP03527A3		3	5.1	1.25			460x25x25		
DPVSP03527A4		4	6.3	1.25			460x25x25		
DPVSP0625A2	600-2500	2	3.1	1.2	500	50	268.2x25x25	N	-40~+80
DPVSP0625A3		3	5.1	1.2			263.2x25x25		
DPVSP0625A4		4	6.3	1.25			263.2x25x25		
DPVSP0727A2	700-2700	2	3.1	1.2	500	50	197x25x25	N	-40~+80
DPVSP0727A3		3	5.1	1.2			195x25x25		
DPVSP0727A4		4	6.3	1.25			195x25x25		
DPVSP0735A2	700-3500	2	3.1	1.2	500	50	197x25x25	N	-40~+80
DPVSP0735A3		3	5.1	1.2			195x25x25		
DPVSP0735A4		4	6.3	1.25			195x25x25		
DPVSP0825A2	800-2500	2	3.1	1.2	500	50	193x25x25	N	-40~+80
DPVSP0825A3		3	5.1	1.2			200x25x25		
DPVSP0825A4		4	6.3	1.25			200x25x25		
DPVSP0827A2	800-2700	2	3.1	1.2	500	50	195x25x25	N	-40~+80
DPVSP0827A3		3	5.1	1.2			195x25x25		
DPVSP0827A4		4	6.3	1.25			195x25x25		



DPV CO

17A16,Jueshi Building, Jiabin Road, Luohu District, Shenzhen 518001, China.

Tel : +86-755-88877009 Fax : +86-755-88877006

E-mail: sales@dpv.co Website: www.dpv.co www.dpvr.com

REV.B