

Coaxial Terminations

- Frequency Range 0 to 6GHz, Up to 500W Power.
- Military, Space and Commercial Applications.
- Good temperature behavior, High aseismatic capability.
- Custom Design Available Upon Request.



Part Number	Freq.Range (GHz)	VSWR Max.	Impedance (Ω)	Power Rating (W)	Size (mm)	Connector Type
DPVCT05SA	DC-3GHz	1.2	50	0.5	Φ 9x13	SMA
	DC-6GHz	1.25				
DPVCT2TA	DC-3GHz	1.2	50	2	Φ 16x28	TNC
	DC-6GHz	1.25				
DPVCT2BA	DC-3GHz	1.2	50	2	Φ 15x28	BNC
	DC-6GHz	1.25				
DPVCT2NA	DC-3GHz	1.2	50	2	Φ 20x36	N
	DC-6GHz	1.25				
DPVCT2SA	DC-3GHz	1.2	50	2	Φ 20x36	SMA
	DC-6GHz	1.25				
DPVCT5sA	DC-3GHz	1.2	50	5	Φ 24x43	SMA
	DC-6GHz	1.25				
DPVCT5TA	DC-3GHz	1.2	50	5	Φ 20x33	TNC
	DC-6GHz	1.25				
DPVCT5NA	DC-3GHz	1.2	50	5	Φ 20x37	N
	DC-6GHz	1.25				
DPVCT5FA	DC-3GHz	1.2	50	5	Φ 14.8x30	Flange
	DC-6GHz	1.25				
DPVCT10NA	DC-3GHz	1.2	50	10	60x60x50	N
	DC-6GHz	1.25				
DPVCT20NA	DC-3GHz	1.2	50	20	70x60x50	N
	DC-6GHz	1.25				
DPVCT50NA	DC-3GHz	1.2	50	50	100x85x60	N
	DC-6GHz	1.25				
DPVCT100NA	DC-3GHz	1.2	50	100	142x120x65	N
	DC-6GHz	1.25				
DPVCT300NA	DC-3GHz	1.2	50	300	300x160x86	N
	DC-6GHz	1.25				
DPVCT500NA	DC-3GHz	1.2	50	500	400x250x97	N
	DC-6GHz	1.25				